

HIL-QUICK® Ring Terminal, insulated, Polycarbonate, A 2,5 - 1,0, 1000 pcs. | 1000

\$\$Marke\$\$ Quetschkabelschuh Ringform, \$\$Isolierstoff\$\$,
\$\$Nennquerschnitt_qmm\$\$, \$\$Verpackungsart_Stk\$\$

Product number 10001 HQ

Weight 0.695kg



Illustrations are for reference only.
Technical specifications may vary and
are subject to change without notice.

Product description

- acc. to DIN 46237
- with flared insulation
- suitable for harmonized wires
- insulation: polycarbonate
- temperature range: -10 °C up to +105 °C
- zero halogen
- UL approved

Product properties

Nominal size	A - 2,5 - 1,0 DIN
Brand	Hil-Quick®
Colour	red
l	17,3 mm
DIN	DIN 46237
d4	4,3 mm
a1	5 mm
Material thickness	0,8 mm
UL-Approval	Yes
Nominal cross section	0,5 - 1,5 mm ²
Temperature resistant	-10 °C - 105 °C
Type of packaging	1000
d3	6 mm
a2	11,3 mm
Insulation material	Polycarbonate
d2	2,7 mm
Version	soldered
Insulation material properties	halogen-free

More images

