

# HIL-SHRINK® 876 2:1 Heat Shrinkable Tubing 1,6/0,8 white | white

876 2:1 dünnwandig, selbstverlöschend

**Product number** 31012

**Weight** 0.832kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

Thin-walled, very flexible, self-extinguishing shrink tubing. Approved to UL 224 VW1, Mil-I-23053, DEF STAN 59-57 issue 3.

- Shrink ratio: 2:1
- Continuous operating temperature: -55 °C to +125 °C
- Shrink temperature: 100 °C
- Material: Polyolefin radiation cross-linked
- UL

## Product properties

|                                         |                                               |
|-----------------------------------------|-----------------------------------------------|
| <b>Approvals</b>                        | Mil-I-23053 , UL 224 , DEF STAN 59-57 Ausg. 3 |
| <b>max after shrink operation Ø d</b>   | 0,8 mm                                        |
| <b>Huges after shrink op. s</b>         | 0,45 mm                                       |
| <b>min. at delivery Ø D</b>             | 1,6 mm                                        |
| <b>Shrink ratio</b>                     | 2:1                                           |
| <b>Shrinking temperature</b>            | 100 °C                                        |
| <b>Material</b>                         | Polyolefin radiation cross-linked             |
| <b>Continuous operating temperature</b> | -55 °C – 125 °C                               |
| <b>Flexibility</b>                      | thin-walled                                   |
| <b>min. at delivery Ø D</b>             | 1/16 Zoll                                     |
| <b>material properties</b>              | self-extinguishing                            |
| <b>Version</b>                          | Coil                                          |
| <b>Type of packaging</b>                | 150                                           |
| <b>Colour</b>                           | white                                         |

## More images

