

# HIL-SHRINK® CFW 3:1 Heat Shrinkable Tubing, medium wall 55/16 black

CFM 3:1 mittelwandig, schwer entflammbar

**Product number** 34150

**Weight** 0.308kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

Medium wall (CFM) heatshrinkable polyolefin adhesive lined tubing ideal for the protection of cable joints and terminations in low voltage power up to 600V.

Applications acc. to ESI-09-11, VDE 0278-95

- shrink ratio: app. 3:1
- permanent operating temperature: -55 °C up to +110 °C
- material: polyolefin cross-linked
- shrink temperature: +120 °C

## Product properties

<b>max after shrink operation Ø d</b>	16 mm
<b>Shrinking temperature</b>	120 °C
<b>Version</b>	sections
<b>Continuous operating temperature</b>	-55 °C – 110 °C
<b>Shrink ratio</b>	3:1
<b>Colour</b>	black
<b>Section length</b>	1 m
<b>Type of packaging</b>	1
<b>Flexibility</b>	medium-walled
<b>Material</b>	Polyolefin radiation cross-linked
<b>Huges after shrink op. s</b>	2,0 mm
<b>Excess length</b>	T
<b>min. at delivery Ø D</b>	55 mm

## More images

