

# HIL-SHRINK® 876 2:1 Heat Shrinkable Tubing 12,7/6,4 red

876 2:1 dünnwandig, selbstverlöschend

**Product number** 31073-        

**Weight** 2.056kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

Thin-walled, very flexible, self-extinguishing shrink tubing. Approved to UL 224 VW1, Mil-I-23053, DEF STAN 59-57 issue 3.

- Shrink ratio: 2:1
- Continuous operating temperature: -55 °C to +125 °C
- Shrink temperature: 100 °C
- Material: Polyolefin radiation cross-linked
- UL

## Product properties

|   |   |
|---|---|
| <b>max after shrink operation Ø d</b>   | 6,4 mm  |
| <b>Approvals</b>                        | Mil-I-23053 , UL 224 , DEF STAN 59-57 Ausg. 3 |
| <b>min. at delivery Ø D</b>             | 1/2 Zoll                                      |
| <b>Colour</b>                           | red   |
| <b>Type of packaging</b>                | 75  |
| <b>Shrink ratio</b>                     | 2:1   |
| <b>Shrinking temperature</b>            | 100 °C  |
| <b>Material</b>                         | Polyolefin radiation cross-linked             |
| <b>Continuous operating temperature</b> | -55 °C - 125 °C                               |
| <b>Huges after shrink op. s</b>         | 0,64 mm                                       |
| <b>Flexibility</b>                      | thin-walled                                   |
| <b>min. at delivery Ø D</b>             | 12,7 mm                                       |
| <b>material properties</b>              | self-extinguishing                            |
| <b>Version</b>                          | Coil  |

## More images

