


# HIL-SHRINK® XTF spool 2:1 Heat Shrinkable Tubing 1,2/0,6 blue

Spule

**Product number** 32204-\_\_

**Weight** 0.694kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

Zero halogen general purpose heat shrinkable tubing for insulation and protection. Self-extinguishing. Approval to standard UL 224 (except clear tubings)

- shrink ratio: 2:1
- permanent operating temperature: -55 °C up to +125 °C
- material: polyolefin
- shrink temperature: +125 °C
- UL
- zero halogen

## Product properties

<b>min. at delivery Ø D</b>	1,2 mm
<b>Shrinking temperature</b>	125 °C
<b>Shrink ratio</b>	2:1
<b>min. at delivery Ø D</b>	3/64 Zoll
<b>Huges after shrink op. s</b>	0,36 mm
<b>Material</b>	Polyolefin
<b>Continuous operating temperature</b>	-55 °C – 125 °C
<b>Colour</b>	blue
<b>Flexibility</b>	thin-walled
<b>material properties</b>	self-extinguishing , halogen-free
<b>max after shrink operation Ø d</b>	0,6 mm
<b>Version</b>	Coil
<b>Type of packaging</b>	150

More images

