

# HIL-SHRINK® XTF spool 2:1 Heat Shrinkable Tubing 3,2/1,6 clear

Spule

**Product number** 32237-  

**Weight** 1.134kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

Zero halogen general purpose heat shrinkable tubing for insulation and protection.

Self-extinguishing. Approval to standard UL 224 (except clear tubings)

- shrink ratio: 2:1
- permanent operating temperature: -55 °C up to +125 °C
- material: polyolefin
- shrink temperature: +125 °C
- UL
- zero halogen

## Product properties

<b>Huges after shrink op. s</b>	0,45 mm
<b>Shrinking temperature</b>	125 °C
<b>min. at delivery Ø D</b>	3,2 mm
<b>Shrink ratio</b>	2:1
<b>min. at delivery Ø D</b>	1/8 Zoll
<b>max after shrink operation Ø d</b>	1,6 mm
<b>Material</b>	Polyolefin
<b>Continuous operating temperature</b>	-55 °C - 125 °C
<b>Flexibility</b>	thin-walled
<b>Colour</b>	transparent
<b>material properties</b>	self-extinguishing , halogen-free
<b>Version</b>	Coil
<b>Type of packaging</b>	150

## More images

