

# Spacing insulator type CT/P, M10, red, 40 mm

TYP CT/P

**Product number** 90123

**Weight** 3.249kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

- made of polyglass-polyester material
- reinforced fibre glass
- self extinguishing
- operating temperature:  $-40\text{ °C} < T < +130\text{ °C}$
- fire resistance: UL94-V0
- threaded bolt: galvanised steel
- UM = max. operating voltage

## Product properties

<b>Typ</b>	CT/P 40
<b>SW</b>	41 mm
<b>max. pressure-carrying capacity</b>	80 kN
<b>Colour</b>	red
<b>Diameter</b>	40 mm
<b>Insulation material properties</b>	self-extinguishing , Reinforced with glass fiber
<b>max. indicate torque</b>	43,0 Nm
<b>A</b>	12 mm
<b>max. pulling force</b>	10 kN
<b>Insulation material</b>	Polyglass-polyester compound
<b>Flame retardancy</b>	UL 94 V-0
<b>Type of packaging</b>	27
<b>Temperature resistant</b>	-40 °C - 130 °C
<b>H</b>	40 mm
<b>max. bending force</b>	7 kN
<b>Creep strength</b>	10 kV
<b>Thread (M)</b>	M10
<b>U_M</b>	1000 V
<b>Discharge voltage</b>	25 kV

## More images

