

HP-ECO Iso insulators for low voltage, M16, black, 100 mm

ECO Isolatoren

Product number 91537

Weight 4.326kg



Illustrations are for reference only.
Technical specifications may vary and
are subject to change without notice.

Product description

- **Insulation:**

- thermosetting polyester reinforced with 20% fiberglass
- self-extinguishing: V0-UL94
- colour: Red RAL 3031

- **Threaded inserts:**

- galvanized steel

- **Final product:**

- rated voltage: 1000 V AC/1500 V DC
- working temperature: -40 °C up to +130 °C

Product properties

| | |
|---------------------------------------|---|
| Thread (M) | M16 |
| Threaded bolt material | Galvanized steel |
| Colour | red |
| Typ | ECO |
| Insulation material properties | self-extinguishing , reinforced with 20 % glass fiber |
| CH | 65 mm |
| D | 50 mm |
| Flame retardancy | UL 94 V-0 |
| Temperature resistant | -40 °C - 130 °C |
| Insulation material | Thermosetting polyester resin |
| R.F. | 10,0 kN |
| H | 100 mm |
| Type of packaging | 10 |
| R.C. | 200 kN |
| R.T. | 30,0 kN |
| Rated voltage DC | 1500 V |
| e | 21 mm |
| f | 25 mm |
| Nominal voltage AC | 1000 V |

More images

