

HP-ECO Iso insulators for low voltage, M4, black, 15 mm

ECO Isolatoren

Product number 91500

Weight 0.276kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

Product description

- **Insulation:**

- thermosetting polyester reinforced with 20% fiberglass
- self-extinguishing: V0-UL94
- colour: Red RAL 3031

- **Threaded inserts:**

- galvanized steel

- **Final product:**

- rated voltage: 1000 V AC/1500 V DC
- working temperature: -40 °C up to +130 °C

Product properties

| | |
|--------------------------------|---|
| R.C. | 15 kN |
| CH | 14 mm |
| Threaded bolt material | Galvanized steel |
| Colour | red |
| Typ | ECO |
| Insulation material properties | self-extinguishing , reinforced with 20 % glass fiber |
| H | 15 mm |
| D | 12 mm |
| Flame retardancy | UL 94 V-0 |
| e | 3 mm |
| Temperature resistant | -40 °C – 130 °C |
| Type of packaging | 50 |
| Insulation material | Thermosetting polyester resin |
| R.T. | 1,5 kN |
| Rated voltage DC | 1500 V |
| Thread (M) | M4 |
| f | 4 mm |
| Nominal voltage AC | 1000 V |
| R.F. | 1,0 kN |

More images

