

# Cable Screw Glands acc. to DIN 46320, PG 16

Kabelverschraubung IP54 DIN 46320

**Product number** 50104

**Weight** 0.698kg



Illustrations are for reference only.  
Technical specifications may vary  
and are subject to change without  
notice.

## Product description

- DIN 46320 for normal applications with soft rubber gasket
- due to the risk of formation of strain fissures the lateral stress on the gland and higher turning moment are to be avoided
- material: impactresistant Polystyrol
- colour: grey RAL 7035
- protection spec.: installation with connection thread gasket IP 66
- temperature resistance: -25 °C up to max. +60 °C

## Product properties

|                                   |                  |
|-----------------------------------|------------------|
| <b>H</b>                          | 28 mm            |
| <b>Thread type</b>                | PG               |
| <b>DIN</b>                        | DIN 46320        |
| <b>Protection spec.</b>           | IP 54            |
| <b>Colour</b>                     | grade (RAL 7035) |
| <b>Temperature resistant</b>      | -20 °C - 60 °C   |
| <b>GL</b>                         | 10 mm            |
| <b>Nominal size</b>               | PG 16            |
| <b>Type of packaging</b>          | 50               |
| <b>Key size</b>                   | 23 / 27 mm       |
| <b>Thread (AG)</b>                | PG 16            |
| <b>Version</b>                    | Impact resistant |
| <b>Material</b>                   | Polystyrene      |
| <b>min. - max. cable diameter</b> | 11 - 14 mm       |

## More images

