

# ShotGland – compression gland, LT type (low temperature), 2 - 3 mm, M 12 x 1,5

Shotgland mit Silikondichtung

**Product number** 50852

**Weight** 0.383kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

- designed especially for the industrial usage where extremely hot or very cold ambient temperatures prevail.
- minimal installation height
- material: brass nickel-plated
- material gasket: silicone
- protection spec.: IP68 (5 bar 30 min)
- temperature resistance: -60 °C up to +180 °C

## Product properties

|                                   |                     |
|-----------------------------------|---------------------|
| <b>H</b>                          | 20,5 - 24,5 mm      |
| <b>Temperature resistant</b>      | -60 °C – 180 °C     |
| <b>Thread (M)</b>                 | M 12 x 1,5          |
| <b>Protection spec.</b>           | IP 68               |
| <b>D</b>                          | 12 mm               |
| <b>Type of packaging</b>          | 50                  |
| <b>L</b>                          | 6 mm                |
| <b>Version</b>                    | with silicone seal  |
| <b>Key size</b>                   | 18 mm               |
| <b>Thread type</b>                | metric              |
| <b>min. - max. cable diameter</b> | 2 - 3 mm            |
| <b>Material</b>                   | Nickel-plated brass |
| <b>E</b>                          | 20 mm               |

## More images

