

Spacing insulator type CT/P, M8, red, 50 mm

TYP CT/P

Product number 90126

Weight 3.946kg



Illustrations are for reference only.
Technical specifications may vary and
are subject to change without notice.

Product description

- made of polyglass-polyester material
- reinforced fibre glass
- self extinguishing
- operating temperature: $-40\text{ °C} < T < +130\text{ °C}$
- fire resistance: UL94-V0
- threaded bolt: galvanised steel
- UM = max. operating voltage

Product properties

| | |
|--|--|
| SW | 41 mm |
| max. pressure-carrying capacity | 80 kN |
| Typ | CT/P 50 |
| U_M | 1500 V |
| Colour | red |
| Diameter | 40 mm |
| Insulation material properties | self-extinguishing , Reinforced with glass fiber |
| A | 12 mm |
| max. indicate torque | 21,5 Nm |
| Thread (M) | M8 |
| max. pulling force | 10 kN |
| Insulation material | Polyglass-polyester compound |
| Flame retardancy | UL 94 V-0 |
| Type of packaging | 27 |
| Temperature resistant | -40 °C - 130 °C |
| Creep strength | 10 kV |
| H | 50 mm |
| Discharge voltage | 35 kV |
| max. bending force | 5 kN |

More images

