

# HIL-SHRINK® 3:1 CCB Heat Shrinkable Tubing Adhesive lined heat shrinkable cable breakouts. Flame retardant 60,0/25 black

CCB 3:1 dickwandig, schwer entflammbar, Abzweigmuffen

**Product number** 34630

**Weight** 0.523kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

Adhesive lined heatshrinkable cable breakouts

- permanent operating temperature: -30 °C up to +70 °C
- material: polyolefin cross-linked
- shrink temperature: +120 °C

### Further Information:

- flame retardant

## Product properties

<b>Shrinking temperature</b>	120 °C
<b>Shrink ratio</b>	3:1
<b>Colour</b>	black
<b>after shrinking L</b>	177 mm
<b>max after shrink operation Ø D1</b>	23 mm
<b>Material</b>	Polyolefin radiation cross-linked
<b>min. at delivery Ø D1</b>	55 mm
<b>min. at delivery Ø D2</b>	25 mm
<b>Delivery condition L</b>	133 mm
<b>material properties</b>	stiff , flame retardant
<b>Type of packaging</b>	10
<b>max after shrink operation Ø D2</b>	8,0 mm
<b>Number of Piggyback Adapters</b>	3
<b>Continuous operating temperature</b>	-30 °C – 70 °C
<b>Flexibility</b>	thick-walled

## More images

