

# HIL-SHRINK 4:1 HTFE Heat Shrinkable Tubing, teflon, 4,8/1,3, transparent

HTFE 4:1 dünnwandig, nicht brennbar, PTFE

**Product number** 32420 L

**Weight** 0.038kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

Very high temperature semi-rigid Teflon® heat shrinkable tubing.

- shrink ratio: 4:1
- permanent operating temperature: -67C °C up to +250 °C
- material: polyteraflourethylen
- shrink temperature: 327 °C

## Product properties

<b>Version</b>	sections
<b>max after shrink operation Ø d</b>	1,3 mm
<b>Huges after shrink op. s</b>	0,3 mm
<b>Type of packaging</b>	1
<b>Section length</b>	1,2 m
<b>material properties</b>	semi-rigid
<b>Shrink ratio</b>	4:1
<b>Shrinking temperature</b>	327 °C
<b>Flexibility</b>	thin-walled
<b>Colour</b>	transparent
<b>min. at delivery Ø D</b>	3/16 Zoll
<b>Continuous operating temperature</b>	-67 °C - 250 °C
<b>Excess length</b>	F
<b>min. at delivery Ø D</b>	4,8 mm
<b>Material</b>	Polyteraflourethylene

## More images

