

EMC cable glands with earthing cone, DIN 89345, M 32 x 1,5 brass

EMV-Kabelverschraubung mit Erdungskronen

Product number 52254

Weight 0.903kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

Product description

- EMC cable gland with internal parts according to DIN 89345
- Permanent contacting of the shielding braid through earthing crowns
- Optimum sealing and strain relief thanks to patented lamella system
- Sealing on the housing with additional EPDM O-ring
- Same sealing ranges and spanner sizes for all screw connections
- Material of screw connection: nickel-plated brass
- Clamping cage material: Polyamide
- Seal material: EPDM
- Protection class: according to EN 60 529: IP 68 up to 5 bar (30 min.)
- Temperature resistance: -20 °C to +100 °C, briefly up to approx. 120 °C
- UL

Product properties

H	36 - 44 mm
Version	with earthing crown
Thread (AG)	M 32 x 1,5
Sealing insert material	EPDM
Protection spec.	IP 68
UL-Approval	Yes
Type of packaging	25
Key size	36 mm
Thread type	metric
GL	8 mm
min. - max. cable diameter	13 - 21 mm
Temperature resistant	-20 °C – 100 °C
Material	Nickel-plated brass

More images

