

Spacing insulator type CS/P, M6, red, 60 mm

TYP CS/P

Product number 90105

Weight 4.53kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

Product description

- made of polyglass-polyester material
- reinforced fibre glass
- self extinguishing
- operating temperature: $-40^{\circ}\text{C} < T < +130^{\circ}\text{C}$
- fire resistance: UL94-V0
- threaded bolt: galvanised steel
- UM = max. operating voltage

Product properties

| | |
|---------------------------------|--|
| U_M | 1500 V |
| Threaded bolt material | Galvanized steel |
| Colour | red |
| Insulation material properties | self-extinguishing , Reinforced with glass fiber |
| H | 60 mm |
| Diameter | 30 mm |
| A | 12 mm |
| Insulation material | Polyglass-polyester compound |
| Flame retardancy | UL 94 V-0 |
| Temperature resistant | -40 °C – 130 °C |
| max. pulling force | 9 kN |
| max. bending force | 1,5 kN |
| Type of packaging | 40 |
| max. pressure-carrying capacity | 40 kN |
| max. indicate torque | 10 - 24 Nm |
| Thread (M) | M6 |
| Discharge voltage | 35 kV |
| Typ | CS/P 60 |
| SW | 30 mm |
| Creep strength | 60 kV |

[More images](#)