

# HP-ECO Insulators, M 10 red 60 mm

ECO Isolatoren

**Product number** 91443

**Weight** 1.761kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

- **Insulation:**

- thermosetting polyester reinforced with 20% fiberglass
- self-extinguishing: V0-UL94
- colour: Red RAL 3031

- **Threaded inserts:**

- galvanized steel

- **Final product:**

- rated voltage: 1000 V AC/1500 V DC
- working temperature: -40 °C up to +130 °C

## Product properties

|                                       |   |
|---------------------------------------|---|
| <b>f</b>                              | 20 mm   |
| <b>R.T.</b>                           | 15,0 kN   |
| <b>Threaded bolt material</b>         | Galvanized steel                                      |
| <b>Colour</b>                         | red   |
| <b>Typ</b>                            | ECO   |
| <b>Insulation material properties</b> | self-extinguishing , reinforced with 20 % glass fiber |
| <b>CH</b>                             | 41 mm   |
| <b>Flame retardancy</b>               | UL 94 V-0   |
| <b>Temperature resistant</b>          | -40 °C - 130 °C                                       |
| <b>Insulation material</b>            | Thermosetting polyester resin                         |
| <b>D</b>                              | 32 mm   |
| <b>H</b>                              | 65 mm   |
| <b>R.F.</b>                           | 10,0 kN   |
| <b>Type of packaging</b>              | 10  |
| <b>R.C.</b>                           | 120 kN  |
| <b>e</b>                              | 12 mm   |
| <b>Rated voltage DC</b>               | 1500 V  |
| <b>Thread (M)</b>                     | M10   |
| <b>Nominal voltage AC</b>             | 1000 V  |

## More images

