

# HIL-BOX® enclosure system including diaphragms, press-on cover, 80 x 40 mm

IP 65 Schnellverschluss

**Product number** 55210 S

**Weight** 0.779kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

Shock resistant enclosures including diaphragms in soft material. Fast locking press-on-cover. Protection IP 65 is assured without any need for glands or drilling holes. The injected membranes guarantee a waterproof seal simply by piercing the membrane with the cable and withdraw slightly to archive a wraparound

- protection spec.: IP 65 acc. DIN EN 60670
- material: base and lid ABS (halogen free) membrane entry rubber
- installation temp.: -15 °C up to +60 °C acc. DIN EN 60670
- temperature resistance: max. 70 °C acc. DIN EN 60695-10-2
- flameprotection: 750 °C acc. DIN EN 60695-2-11

## Product properties

|                                |              |
|--------------------------------|--------------|
| <b>Membranes</b>               | 4 + 2        |
| <b>Lid colour</b>              | black        |
| <b>C</b>                       | 40 mm        |
| <b>max. diaphragm diameter</b> | 23           |
| <b>DIN</b>                     | DIN EN 60529 |
| <b>Type of packaging</b>       | 10           |
| <b>A</b>                       | 80 mm        |
| <b>Protection spec.</b>        | IP 65        |

## More images

