


# Preinsulated wire end sleeves, 0,34 L turquoise, 500 pcs. | 500

mit Kunststoffkragen

**Product number** 08102

**Weight** 0.031kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

- acc. to DIN 46228 part 4 (0,5 up to 50 mm<sup>2</sup>)
- feed mouth of polyamide
- heat resistant up to 105 °C
- for wire 0,14 up to 150 mm<sup>2</sup>
- sizes: K = short, N = normal, HL = half long, L = long, SL = special length
- zero halogen

## Product properties

<b>Colour</b>	turquoise
<b>Version</b>	with insulation
<b>d1</b>	0.80 mm
<b>S1</b>	0,15 mm
<b>d3</b>	2,0 mm
<b>Identifying Colour</b>	A
<b>I2</b>	8,0 mm
<b>S2</b>	0,25 mm
<b>Insulation material</b>	Polyamide
<b>Length</b>	Long
<b>I1</b>	12.5 mm
<b>DIN</b>	DIN 46288 Part 4
<b>AWG</b>	22
<b>Nominal cross section</b>	0,34 L mm <sup>2</sup>
<b>Type of packaging</b>	500
<b>Insulation material properties</b>	halogen-free

## More images

