

# HIL-QUICK® Ring Terminal, insulated, Polycarbonate, A 3,5 - 1,0, 1000 pcs. | 1000

\$\$\$Marke\$\$\$ Quetschkabelschuh Ringform, \$\$Isolierstoff\$\$, \$\$Nennquerschnitt\_qmm\$\$, \$\$Verpackungsart\_Stk\$\$\$

**Product number** 10003 HQ

**Weight** 0.645kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

- acc. to DIN 46237
- with flared insulation
- suitable for harmonized wires
- insulation: polycarbonate
- temperature range: -10 °C up to +105 °C
- zero halogen
- UL approved

## Product properties

|                                       |                           |
|---------------------------------------|---------------------------|
| <b>Brand</b>                          | Hil-Quick®                |
| <b>Nominal size</b>                   | A - 3,5 - 1,0 DIN         |
| <b>Colour</b>                         | red                       |
| <b>l</b>                              | 17,3 mm                   |
| <b>DIN</b>                            | DIN 46237                 |
| <b>d4</b>                             | 4,3 mm                    |
| <b>a1</b>                             | 5 mm                      |
| <b>Material thickness</b>             | 0,8 mm                    |
| <b>UL-Approval</b>                    | Yes                       |
| <b>Nominal cross section</b>          | 0,5 - 1,5 mm <sup>2</sup> |
| <b>d2</b>                             | 3,7 mm                    |
| <b>Temperature resistant</b>          | -10 °C – 105 °C           |
| <b>Type of packaging</b>              | 1000                      |
| <b>d3</b>                             | 6 mm                      |
| <b>a2</b>                             | 11,3 mm                   |
| <b>Insulation material</b>            | Polycarbonate             |
| <b>Version</b>                        | soldered                  |
| <b>Insulation material properties</b> | halogen-free              |

## More images

