

EMC Cable Screw Gland, UNI HF Dicht, PG 13,5 EMC, 7,0 - 10,5 cable

EMV-Kabelverschraubung UNI HF Dicht

Product number 52067

Weight 1.859kg



Illustrations are for reference only.
Technical specifications may vary and
are subject to change without notice.

Product description

The functional effect of the gland is only achieved by a low-ohm transition resistance between the cable and line leads and the wall of the electrical unit, i. e. clean the contact surfaces or even better provide, permanent bonding from inside by fitting lock nuts with equipotential bonding.

- with sealing out of TPE
- material: brass, nickel-plated
- protection spec.: IP 68 up to 10 bar
- temperature resistance: -20 °C up to +105 °C

Further information:

- **Index A:** stripped cable sheath
- **Index B:** continuous cable sheath

Product properties

H	21 mm
Thread type	PG
Thread (AG)	PG 13,5
Protection spec.	IP 68
Sealing insert material	TPE
Version	with iris feather
Type of packaging	50
min. - max. cable diameter	10,5 - 7 mm
Cable sheath	abgesetzt
Screen diameter max.-min.	8 - 3 mm
GL	6,5 mm
Temperature resistant	-20 °C - 105 °C
Material	Nickel-plated brass

More images

