

HIL-QUICK® Ring Terminal, insulated, Polycarbonate, A 4 - 2,5, 1000 pcs. | 1000

\$\$\$Marke\$\$\$ Quetschkabelschuh Ringform, \$\$\$Isolierstoff\$\$\$,
\$\$\$Nennquerschnitt_qmm\$\$\$, \$\$\$Verpackungsart_Stk\$\$\$

Product number 10012 HQ

Weight 0.895kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

Product description

- acc. to DIN 46237
- with flared insulation
- suitable for harmonized wires
- insulation: polycarbonate
- temperature range: -10 °C up to +105 °C
- zero halogen
- UL approved

Product properties

Brand	Hil-Quick®
l	18,3 mm
d2	4,3 mm
Nominal cross section	> 1 - 2,5 mm ²
DIN	DIN 46237
a1	5 mm
Material thickness	0,8 mm
d4	5 mm
UL-Approval	Yes
Temperature resistant	-10 °C – 105 °C
Type of packaging	1000
Colour	blue
a2	11,3 mm
Insulation material	Polycarbonate
Version	soldered
d3	8 mm
Nominal size	A - 4 - 2,5 DIN
Insulation material properties	halogen-free

More images

