

# HIL-SHRINK® HKN 2:1 Heat Shrinkable Tubing 6,4/3,2 clear

HKN 2:1 dünnwandig, selbstverlöschend

**Product number** 31650 L

**Weight** 0.047kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

Mechanically tough, high temperature, semi-rigid heat shrinkable tubing in polyvenylidene fluoride. Acc. to UL 224 VW1, SAE-AMS-DTL 23053/18 class 2.

- shrink ratio: 2:1
- permanent operating temperature: -55 °C up to +175 °C
- material: polyvenylidene fluoride
- shrink temperature: 170 °C

## Product properties

<b>Approvals</b>	AMS-DTL-23053/8 , UL 224 , DEF STAN 59-57 , VW 1 , VG 95343 Pt 5
<b>Version</b>	sections
<b>Huges after shrink op. s</b>	0,3 mm
<b>Type of packaging</b>	1
<b>Section length</b>	1,2 m
<b>Shrink ratio</b>	2:1
<b>Flexibility</b>	thin-walled
<b>Colour</b>	transparent
<b>Shrinking temperature</b>	170 °C
<b>Excess length</b>	T
<b>Material</b>	Polyvenylidene fluoride radiation cross-linked
<b>min. at delivery Ø D</b>	6,4 mm
<b>Continuous operating temperature</b>	-55 °C – 175 °C
<b>material properties</b>	self-extinguishing
<b>max after shrink operation Ø d</b>	3,2 mm
<b>min. at delivery Ø D</b>	1/4 Zoll

## More images

