

# Spacing insulator type CPE, M10, red, 80 mm

TYP CPE

**Product number** 90146

**Weight** 3.638kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

- made of polyglass-polyester material
- reinforced fibre glass
- self extinguishing
- operating temperature: -40 °C to +130 °C
- fire resistance: UL94-V0
- threaded bolt: galvanised steel
- UM = max. operating voltage

## Product properties

<b>Diameter</b>	60 mm
<b>Threaded bolt material</b>	Galvanized steel
<b>Colour</b>	red
<b>max. pulling force</b>	23 kN
<b>Creep strength</b>	25 kV
<b>Insulation material properties</b>	self-extinguishing , Reinforced with glass fiber
<b>max. indicate torque</b>	24 - 55 Nm
<b>Insulation material</b>	Polyglass-polyester compound
<b>Flame retardancy</b>	UL 94 V-0
<b>Type of packaging</b>	8
<b>Temperature resistant</b>	-40 °C – 130 °C
<b>max. bending force</b>	9 kN
<b>SW</b>	60 mm
<b>max. pressure-carrying capacity</b>	120 kN
<b>Discharge voltage</b>	50 kV
<b>U_M</b>	5000 V
<b>A</b>	19 mm
<b>Typ</b>	CPE 80
<b>Thread (M)</b>	M10
<b>H</b>	80 mm

## More images

