

EMC cable glands with earthing cone, DIN 89345, M 20 x 1,5 brass

EMV-Kabelverschraubung mit Erdungskronen

Product number 52252

Weight 1.298kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

Product description

- EMC cable gland with internal parts according to DIN 89345
- Permanent contacting of the shielding braid through earthing crowns
- Optimum sealing and strain relief thanks to patented lamella system
- Sealing on the housing with additional EPDM O-ring
- Same sealing ranges and spanner sizes for all screw connections
- Material of screw connection: nickel-plated brass
- Clamping cage material: Polyamide
- Seal material: EPDM
- Protection class: according to EN 60 529: IP 68 up to 5 bar (30 min.)
- Temperature resistance: -20 °C to +100 °C, briefly up to approx. 120 °C
- UL

Product properties

| | |
|-----------------------------------|---------------------|
| Version | with earthing crown |
| Sealing insert material | EPDM |
| Protection spec. | IP 68 |
| min. - max. cable diameter | 6 - 13 mm |
| H | 29 - 37 mm |
| Type of packaging | 50 |
| UL-Approval | Yes |
| Thread type | metric |
| GL | 6 mm |
| Key size | 24 mm |
| Temperature resistant | -20 °C – 100 °C |
| Material | Nickel-plated brass |
| Thread (AG) | M 20 x 1,5 |

More images

