

# HIL-QUICK® Spade Terminal, insulated, Polycarbonate unbrazed, C 4 - 2,5, 1000 pcs. | 1000

Polycarbonat ungelötet

**Product number** 10062 SQ

**Weight** 0.895kg



Illustrations are for reference only.  
Technical specifications may vary  
and are subject to change without  
notice.

## Product description

- with flared insulation
- suitable for harmonized wires
- insulation: polycarbonate unbrazed
- temperature range: -10 °C up to +105 °C

## Product properties

|                              |                           |
|------------------------------|---------------------------|
| <b>l</b>                     | 18,3 mm                   |
| <b>d2</b>                    | 4,3 mm                    |
| <b>Nominal cross section</b> | > 1 - 2,5 mm <sup>2</sup> |
| <b>a1</b>                    | 5 mm                      |
| <b>Material thickness</b>    | 0,8 mm                    |
| <b>d4</b>                    | 5 mm                      |
| <b>Type of packaging</b>     | 1000                      |
| <b>Colour</b>                | blue                      |
| <b>a2</b>                    | 11,3 mm                   |
| <b>d3</b>                    | 7 mm                      |
| <b>Insulation material</b>   | Polycarbonate             |
| <b>Nominal size</b>          | C - 4 - 2,5 DIN           |
| <b>Version</b>               | unsoldered                |

## More images

