

# HILPRESS-TEXO® Cable Screw Glands, Polyamide, PG 36 | gray

TEXO IP68

**Product number** 51517

**Weight** 0.701kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

- with stress relief and integrated connection lip gasketed nitrile rubber.
- Ansealed wire test acc. to DIN EN 60695-2-11
- material: polyamide
- protection spec.: IP 68 up to 5 bar (30 min.)
- temperature resistance: -20°C up to +80°C, short time up to 120 °C
- flame protection: 750 °C
- UL
- zero halogen

The integrated sealing lip makes the connection thread sealing ring (M 12 x 15 - M32 x 1.5) unnecessary. Only for smooth surfaces, otherwise the use of a sealing ring is recommended.

## Product properties

<b>H</b>	56 - 65 mm
<b>Thread type</b>	PG
<b>Key size</b>	53 mm
<b>Protection spec.</b>	IP 68
<b>Temperature resistant</b>	-20 °C – 80 °C
<b>UL-Approval</b>	Yes
<b>Version</b>	Standard
<b>GL</b>	14 mm
<b>Material</b>	Polyamide
<b>Type of packaging</b>	10
<b>Colour</b>	gray
<b>min. - max. cable diameter</b>	22 - 32 mm
<b>Nominal size</b>	PG 36
<b>Thread (AG)</b>	PG 36
<b>Brand</b>	TEXO®
<b>material properties</b>	halogen-free

More images

