# Spacing insulator type DP/P, M12, red, 50 mm



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

**Product number** 90048
**Weight** 3.498kg

## Product description

- made of Polyglas-polyester material
- reinforced with fibreglass
- colour: red
- self extinguishing
- operating temperature: -40 °C < T < +130 °C
- fire resistance: UL94-V0
- UM = max. permissable operating voltage

## Product properties

| | |
|---|---|
| **A** | 13 mm |
| **Creep strength** | 12 kV |
| **max. bending force** | 4,5 kN |
| **Threaded bolt material** | Galvanized steel |
| **Colour** | red |
| **max. pressure-carrying capacity** | 68 kN |
| **Discharge voltage** | 40 kV |
| **Insulation material properties** | self-extinguishing , Reinforced with glass fiber |
| **SW** | 36 mm |
| **U_M** | 2000 V |
| **Thread (M)** | M12 |
| **Insulation material** | Polyglass-polyester compound |
| **Flame retardancy** | UL 94 V-0 |
| **Temperature resistant** | -40 °C – 130 °C |
| **max. indicate torque** | 85,0 Nm |
| **Typ** | DB/P 50 |
| **max. pulling force** | 8,5 kN |
| **d1** | 29 mm |
| **H** | 50 mm |
| **Type of packaging** | 36 |

## More images






