

# EMC Cable Screw Glands UNI HF Dicht, brass, metric, 13,0 - 9,0 cable, M 32 x 1,5 brass

EMV-Kabelverschraubung UNI HF Dicht

**Product number** 52213

**Weight** 2.662kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

The functional effect of the gland is only achieved by a low-ohm transition resistance between the cable and line lead-ins and the wall of the electrical unit, i. e. clean the contact surfaces or even better provide permanent bonding from inside by fitting lock nuts with equipotential bonding

- material: brass, nickel-plated
- material sealing insert: TPE
- protection spec.: IP 68 up to 10 bar
- temperature resistance: -20 °C up to +105 °C

## Product properties

<b>Screen diameter max.-min.</b>	12,0 - 7,5 mm
<b>Thread (AG)</b>	M 32 x 1,5
<b>Protection spec.</b>	IP 68
<b>Sealing insert material</b>	TPE
<b>Version</b>	with iris feather
<b>Type of packaging</b>	25
<b>min. - max. cable diameter</b>	13 - 9 mm
<b>GL</b>	7 mm
<b>Thread type</b>	metric
<b>Cable sheath</b>	durchgängig
<b>H</b>	25 mm
<b>Temperature resistant</b>	-20 °C – 105 °C
<b>Material</b>	Nickel-plated brass

## More images

