

# HIL-BOX® enclosure system with smooth walls, nylon-hinged screws, grey, 460 x 380 x 120 mm

glatte Gehäusesseiten

**Product number** 55540

**Weight** 2.131kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

Plain sides hock resistant enclosures with cover fixed by nylon-screws. The unscrewing of the nylon screws allows to open the lid in 2 directions depending on the used screws. The screws are used as hinge and allow a fast opening of the enclosure.

- protection spec.: IP 65 acc. DIN EN 60529
- material: base and lid ABS (UV resistant), transparent lid PC, screws PA
- installation temp.: -15 °C up to +60 °C acc. DIN EN 60670
- temperature resistance: max. +70 °C acc. DIN EN 60695-10-2
- flame protection: 650 °C acc. DIN EN 60695-2-11
- zero halogen

### Further information:

- screws included

## Product properties

<b>G</b>	80 mm
<b>C</b>	120 mm
<b>A</b>	460 mm
<b>Type of packaging</b>	1
<b>D</b>	50 mm
<b>DIN</b>	DIN EN 60529
<b>Lid colour</b>	gray
<b>Protection spec.</b>	IP 65
<b>b</b>	380 mm

## More images

