

# HIL-QUICK® Female Push on Terminal, insulated, Polycarbonate, 2,8 - 0,8 - 1,0, 1000 pcs. | 1000

Polycarbonat

**Product number** 10181 HQ

**Weight** 0.545kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

- acc. to DIN 46245, part 1-3 and similar
- double crimp
- insulation: polycarbonate
- temperature range: -10 °C up to +105 °C
- zero halogen

## Product properties

<b>Terminal Width</b>	2,8 mm
<b>Terminal Thickness</b>	0,8 mm
<b>l</b>	18 mm
<b>a2</b>	10 mm
<b>Colour</b>	red
<b>Nominal cross section</b>	0,5 - 1,5 mm <sup>2</sup>
<b>l1</b>	6 mm
<b>Temperature resistant</b>	-10 °C - 105 °C
<b>Version</b>	with metallic insulation support
<b>Type of packaging</b>	1000
<b>Insulation material</b>	Polycarbonate
<b>Material</b>	Brass
<b>Insulation material properties</b>	halogen-free
<b>Nominal size</b>	1 mm <sup>2</sup>
<b>Material thickness</b>	0,3 mm

## More images

