

HIL-QUICK® Ring Terminal, insulated, Polycarbonate, A 8 - 1,0, 1000 pcs. | 1000

\$\$\$Marke\$\$\$ Quetschkabelschuh Ringform, \$\$\$Isolierstoff\$\$\$,
\$\$\$Nennquerschnitt_qmm\$\$\$, \$\$\$Verpackungsart_Stk\$\$\$

Product number 10007 HQ

Weight 1.413kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

Product description

- acc. to DIN 46237
- with flared insulation
- suitable for harmonized wires
- insulation: polycarbonate
- temperature range: -10 °C up to +105 °C
- zero halogen
- UL approved

Product properties

Brand	Hil-Quick®
Colour	red
DIN	DIN 46237
d4	4,3 mm
a1	5 mm
Material thickness	0,8 mm
UL-Approval	Yes
Nominal cross section	0,5 - 1,5 mm ²
Temperature resistant	-10 °C – 105 °C
Type of packaging	1000
Nominal size	A - 8 - 1,0 DIN
l	23,3 mm
a2	11,3 mm
Insulation material	Polycarbonate
d3	14 mm
Version	soldered
d2	8,4 mm
Insulation material properties	halogen-free

More images

