

# HIL-SHRINK® HQ 4:1 isk Heat Shrinkable Tubing 12,0/3,0 black | sections

HQ 4:1 isk dünnwandig, selbstverlöschend, mit Innenkleber

**Product number** 31720 L

**Weight** 0.042kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

Thin wall semi rigid heat shrinkable tubings self extinguishing, with adhesive inner liner.

- shrink ratio: 4:1
- permanent operating temperature: -55 °C up to +110 °C
- material: polyolefin cross-linked
- shrink temperature: 100 °C

## Product properties

<b>Glue</b>	0,5 mm
<b>min. at delivery Ø D</b>	12 mm
<b>max after shrink operation Ø d</b>	3 mm
<b>Version</b>	sections
<b>Continuous operating temperature</b>	-55 °C – 110 °C
<b>Colour</b>	black
<b>Section length</b>	1 m
<b>Type of packaging</b>	1
<b>material properties</b>	semi-rigid , with hot-melt adhesive coating on the inside , self-extinguishing , halogen-free
<b>Shrink ratio</b>	4:1
<b>Shrinking temperature</b>	100 °C
<b>Material</b>	Polyolefin radiation cross-linked
<b>Huges after shrink op. s</b>	1,30 mm
<b>Flexibility</b>	thin-walled
<b>Excess length</b>	T

## More images

