

# HP-ECO Iso insulators for low voltage, M10, black, 40 mm

ECO Isolatoren

**Product number** 91517

**Weight** 2.726kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

- **Insulation:**

- thermosetting polyester reinforced with 20% fiberglass
- self-extinguishing: V0-UL94
- colour: Red RAL 3031

- **Threaded inserts:**

- galvanized steel

- **Final product:**

- rated voltage: 1000 V AC/1500 V DC
- working temperature: -40 °C up to +130 °C

## Product properties

<b>f</b>	11 mm
<b>D</b>	40 mm
<b>R.T.</b>	15,0 kN
<b>Threaded bolt material</b>	Galvanized steel
<b>Colour</b>	red
<b>Typ</b>	ECO
<b>Insulation material properties</b>	self-extinguishing , reinforced with 20 % glass fiber
<b>Flame retardancy</b>	UL 94 V-0
<b>Temperature resistant</b>	-40 °C - 130 °C
<b>Insulation material</b>	Thermosetting polyester resin
<b>H</b>	40 mm
<b>R.F.</b>	6,0 kN
<b>Type of packaging</b>	25
<b>R.C.</b>	120 kN
<b>e</b>	12 mm
<b>Rated voltage DC</b>	1500 V
<b>CH</b>	46 mm
<b>Thread (M)</b>	M10
<b>Nominal voltage AC</b>	1000 V

## More images

