

# Spacing insulator type CT/P, M8, red, 60 mm

TYP CT/P

**Product number** 90130

**Weight** 3.205kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

- made of polyglass-polyester material
- reinforced fibre glass
- self extinguishing
- operating temperature:  $-40\text{ °C} < T < +130\text{ °C}$
- fire resistance: UL94-V0
- threaded bolt: galvanised steel
- UM = max. operating voltage

## Product properties

|  |  |
|--|--|
| <b>SW</b>                              | 41 mm  |
| <b>max. pressure-carrying capacity</b> | 80 kN  |
| <b>U_M</b>                             | 1500 V   |
| <b>Colour</b>                          | red  |
| <b>Diameter</b>                        | 40 mm  |
| <b>Insulation material properties</b>  | self-extinguishing , Reinforced with glass fiber |
| <b>H</b>                               | 60 mm  |
| <b>A</b>                               | 18 mm  |
| <b>max. indicate torque</b>            | 21,5 Nm  |
| <b>Thread (M)</b>                      | M8   |
| <b>max. pulling force</b>              | 10 kN  |
| <b>Insulation material</b>             | Polyglass-polyester compound                     |
| <b>Flame retardancy</b>                | UL 94 V-0  |
| <b>Temperature resistant</b>           | -40 °C - 130 °C                                  |
| <b>Creep strength</b>                  | 10 kV  |
| <b>max. bending force</b>              | 3,7 kN   |
| <b>Discharge voltage</b>               | 35 kV  |
| <b>Type of packaging</b>               | 18   |
| <b>Typ</b>                             | CT/P 60  |

## More images

