

# EMC cable glands with earthing cone, DIN 89345, M 50 x 1,5 brass

EMV-Kabelverschraubung mit Erdungskronen

**Product number** 52256

**Weight** 1.166kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

- EMC cable gland with internal parts according to DIN 89345
- Permanent contacting of the shielding braid through earthing crowns
- Optimum sealing and strain relief thanks to patented lamella system
- Sealing on the housing with additional EPDM O-ring
- Same sealing ranges and spanner sizes for all screw connections
- Material of screw connection: nickel-plated brass
- Clamping cage material: Polyamide
- Seal material: EPDM
- Protection class: according to EN 60 529: IP 68 up to 5 bar (30 min.)
- Temperature resistance: -20 °C to +100 °C, briefly up to approx. 120 °C
- UL

## Product properties

<b>min. - max. cable diameter</b>	21 - 35 mm
<b>GL</b>	9 mm
<b>Key size</b>	55 mm
<b>Version</b>	with earthing crown
<b>Sealing insert material</b>	EPDM
<b>Protection spec.</b>	IP 68
<b>UL-Approval</b>	Yes
<b>Type of packaging</b>	10
<b>Thread type</b>	metric
<b>Thread (AG)</b>	M 50 x 1,5
<b>Temperature resistant</b>	-20 °C – 100 °C
<b>H</b>	51 - 62 mm
<b>Material</b>	Nickel-plated brass

More images

