

# HIL-BOX®enclosure system including diaphragms, screwed cover, grey, 190 x 145 x 135 mm

IP 65 Schraubdeckel

**Product number** 55300

**Weight** 0.473kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

These are impact-resistant enclosures with soft self-sealing diaphragm entries, the cover of which is for screwing on.

- protection class: IP 65 according to DIN EN 60529.
- material: Enclosure and cover ABS (UV protected, halogen-free), diaphragm entry rubber
- installation temperature: -15 °C to +60 °C acc. to DIN EN 60670
- temperature resistance: up to max. 70 °C acc. to DIN EN 60695-10-2
- flame resistance: 650 °C acc. to DIN EN 60695-2-11

### Further information:

- Screws made of stainless steel
- Screws included in delivery
- Attention: Articles 55290 - 55311 are with high lid

## Product properties

<b>A</b>	190 mm
<b>Type of packaging</b>	1
<b>Membranes</b>	10
<b>b</b>	145 mm
<b>DIN</b>	DIN EN 60529
<b>Lid colour</b>	gray
<b>Protection spec.</b>	IP 65 pod?a DIN EN 60529
<b>max. diaphragm diameter</b>	37
<b>C</b>	135 mm

## More images

