

# EMC Cable Screw Glands UNI HF Dicht, brass, metric, 18,0 - 14,0 cable, M 40 x 1,5 brass

EMV-Kabelverschraubung UNI HF Dicht

**Product number** 52216

**Weight** 0.873kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

The functional effect of the gland is only achieved by a low-ohm transition resistance between the cable and line leads and the wall of the electrical unit, i. e. clean the contact surfaces or even better provide permanent bonding from inside by fitting lock nuts with equipotential bonding

- material: brass, nickel-plated
- material sealing insert: TPE
- protection spec.: IP 68 up to 10 bar
- temperature resistance: -20 °C up to +105 °C

## Product properties

<b>Protection spec.</b>	IP 68
<b>Sealing insert material</b>	TPE
<b>Screen diameter max.-min.</b>	17,0 - 13,0 mm
<b>Version</b>	with iris feather
<b>Cable sheath</b>	abgesetzt
<b>Type of packaging</b>	10
<b>Thread (AG)</b>	M 40 x 1,5
<b>Thread type</b>	metric
<b>GL</b>	8 mm
<b>H</b>	27 mm
<b>Temperature resistant</b>	-20 °C - 105 °C
<b>min. - max. cable diameter</b>	18 - 14 mm
<b>Material</b>	Nickel-plated brass

## More images

