

HP-ECO Iso insulators for low voltage with long thread, M6, black, 20 mm

ECO Isolatoren

Product number 91604 Weight 0.776kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

Product description

- Insulation:
- thermosetting polyester reinforced with 20% fiberglass
- self-extinguishing: V0-UL94
- colour: Red RAL 3031
- Threaded inserts:
- galvanized steel
- Final product:
- rated voltage: 1000 V AC/1500 V DC
- \bullet working temperature: -40 °C up to +130 °C



Product properties

f 5 mm

Threaded bolt material Galvanized steel

 Colour
 red

 Typ
 ECO

 D
 20 mm

Insulation material properties self-extinguishing, reinforced with 20 % glass fiber

R.F. 2,8 kN R.T. 4,5 kN UL 94 V-0 Temperature resistant $-40 \, ^{\circ}\text{C} - 130 \, ^{\circ}\text{C}$

Type of packaging 50

Insulation material Thermosetting polyester resin

 Thread (M)
 M6

 R.C.
 45 kN

 H
 20 mm

 Rated voltage DC
 1500 V

 e
 8,5 mm

 CH
 21 mm

 Nominal voltage AC
 1000 V



More images







