

HP-ECO Insulators, M 10 red 35 mm

ECO Isolatoren

Product number 91040

Weight 1.127kg



Illustrations are for reference only.
Technical specifications may vary and
are subject to change without notice.

Product description

- **Insulation:**

- thermosetting polyester reinforced with 20% fiberglass
- self-extinguishing: V0-UL94
- colour: Red RAL 3031

- **Threaded inserts:**

- galvanized steel

- **Final product:**

- rated voltage: 1000 V AC/1500 V DC
- working temperature: -40 °C up to +130 °C

Product properties

| | |
|--------------------------------|---|
| D | 35 mm |
| Threaded bolt material | Galvanized steel |
| Colour | red |
| Typ | ECO |
| Insulation material properties | self-extinguishing , reinforced with 20 % glass fiber |
| max. indicate torque | 50 Nm |
| CH | 41 mm |
| R.F. | 6,7 kN |
| e | 10 mm |
| Flame retardancy | UL 94 V-0 |
| Temperature resistant | -40 °C - 130 °C |
| Insulation material | Thermosetting polyester resin |
| Type of packaging | 10 |
| H | 35 mm |
| Rated voltage DC | 1500 V |
| f | 12 mm |
| Thread (M) | M10 |
| R.T. | 7,9 kN |
| R.C. | 130 kN |
| Nominal voltage AC | 1000 V |

More images

