

# HIL-SHRINK® 2:1 Heat Shrinkable Tubing, 1,2/0,6 green | green

Box

**Product number** 30096

**Weight** 0.252kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

Thin wall flexible heat shrinkable tubings, self extinguishing acc. to UL 224, on small spools in dispenser box

- shrink ratio: 2:1
- permanent operating temperature: -55 °C up to +125 °C
- material: polyolefin cross-linked
- shrink temperature: +120 °C

### Further information:

- ATTENTION: the transparent tubings are not self extinguishing!

## Product properties

<b>Shrinking temperature</b>	120 °C
<b>Approvals</b>	UL 224
<b>min. at delivery Ø D</b>	1,2 mm
<b>Huges after shrink op. s</b>	0,45 mm
<b>Type of packaging</b>	1
<b>Shrink ratio</b>	2:1
<b>min. at delivery Ø D</b>	3/64 Zoll
<b>Material</b>	Polyolefin radiation cross-linked
<b>Continuous operating temperature</b>	-55 °C – 125 °C
<b>Flexibility</b>	thin-walled
<b>Coil size</b>	15 m/Box
<b>material properties</b>	self-extinguishing
<b>Version</b>	Box
<b>Colour</b>	green
<b>max after shrink operation Ø d</b>	0,6 mm

## More images

