

# EMC Cable Screw Gland, UNI HF Dicht, PG 36 EMC, 24,0 - 28,0 cable

EMV-Kabelverschraubung UNI HF Dicht

**Product number** 52081

**Weight** 2.012kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

The functional effect of the gland is only achieved by a low-ohm transition resistance between the cable and line lead-ins and the wall of the electrical unit, i. e. clean the contact surfaces or even better provide, permanent bonding from inside by fitting lock nuts with equipotential bonding.

- with sealing out of TPE
- material: brass, nickel-plated
- protection spec.: IP 68 up to 10 bar
- temperature resistance: -20 °C up to +105 °C

### Further information:

- **Index A:** stripped cable sheath
- **Index B:** continuous cable sheath

## Product properties

|                                   |                     |
|-----------------------------------|---------------------|
| <b>H</b>                          | 28 mm               |
| <b>GL</b>                         | 9 mm                |
| <b>Thread type</b>                | PG                  |
| <b>Protection spec.</b>           | IP 68               |
| <b>Sealing insert material</b>    | TPE                 |
| <b>Version</b>                    | with iris feather   |
| <b>Cable sheath</b>               | abgesetzt           |
| <b>Type of packaging</b>          | 10                  |
| <b>Thread (AG)</b>                | PG 36               |
| <b>Temperature resistant</b>      | -20 °C – 105 °C     |
| <b>min. - max. cable diameter</b> | 28 - 24 mm          |
| <b>Screen diameter max.-min.</b>  | 25,5 - 18 mm        |
| <b>Material</b>                   | Nickel-plated brass |

More images

