

HP-MASTER® Stripping and crimping machine KARL, for wire end sleeves, Standard | Standard

HP-MASTER®-Abisolier- und Crimpautomat KARL für Aderendhülsen

Product number 12500

Weight 2.32kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

Product description

- with crimping tools of cross-sections 0.5 / 0.75 / 1.0 / 1.5 mm² as standard.
- Extension sets available for processing cross-sections of 0.25 / 0.34 / 0.25 and 4 mm²
- Universal for ferrules with a length of 6 - 12 mm
- Cross-section can be adjusted in a few simple steps
- Stripping and crimping is carried out in a single operation
- all adjustable parameters are automatically set correctly when the crimping dies are changed
- Modular design
- High reliability thanks to the use of non-locking components

Extension sets with case

- Cross-section 0.25 / 0.34 mm² (length 6 + 8)
- Cross-section 2.5 mm² (length 8 - 12 mm)
- Cross-section 4 mm² (length 10 and 12 mm)

Product properties

Mains connection	110 - 240 V / 50 - 60 Hz
max. power consumption	70 W
Type of packaging	1
Cross section	0,5 – 1,5 mm ²
Version	Standard
Dimensions (L x W x H)	550 x 250 x 412 mm
Compressed air connection	5 bar
Crimping length	6 - 12 mm
Cycle time	1 s

More images

