

# HIL-QUICK® Male Push on Terminal, insulated, Polycarbonate unbrazed, 6,3 - 0,8 - 1,0, 1000 pcs. | 1000

Polycarbonat ungelötet

**Product number** 10340 SQ

**Weight** 0.985kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

- insulation: polycarbonate
- temperature resistance: -10 °C up to +105 °C
- double crimp: Quick In® without copper sleeve

## Product properties

|                              |                                     |
|------------------------------|-------------------------------------|
| <b>l1</b>                    | 7,5 mm                              |
| <b>Terminal Thickness</b>    | 0,8 mm                              |
| <b>a2</b>                    | 10 mm                               |
| <b>Colour</b>                | red                                 |
| <b>Material thickness</b>    | 0,38 mm                             |
| <b>Terminal Width</b>        | 6,3 mm                              |
| <b>Nominal cross section</b> | > 1 - 1,5 mm <sup>2</sup>           |
| <b>Temperature resistant</b> | -10 °C - 105 °C                     |
| <b>Version</b>               | without metallic insulation support |
| <b>Type of packaging</b>     | 1000                                |
| <b>Insulation material</b>   | Polycarbonate                       |
| <b>l</b>                     | 22 mm                               |
| <b>Material</b>              | Brass                               |
| <b>Nominal size</b>          | 1 mm <sup>2</sup>                   |

## More images

