

# EMC Cable Screw Gland, UNI HF Dicht, PG 42 EMC, 36,0 - 40,0 cable

EMV-Kabelverschraubung UNI HF Dicht

**Product number** 52084

**Weight** 2.687kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

The functional effect of the gland is only achieved by a low-ohm transition resistance between the cable and line leads and the wall of the electrical unit, i. e. clean the contact surfaces or even better provide, permanent bonding from inside by fitting lock nuts with equipotential bonding.

- with sealing out of TPE
- material: brass, nickel-plated
- protection spec.: IP 68 up to 10 bar
- temperature resistance: -20 °C up to +105 °C

### Further information:

- **Index A:** stripped cable sheath
- **Index B:** continuous cable sheath

## Product properties

<b>Thread type</b>	PG
<b>min. - max. cable diameter</b>	40 - 36 mm
<b>GL</b>	10 mm
<b>Protection spec.</b>	IP 68
<b>Sealing insert material</b>	TPE
<b>H</b>	30 mm
<b>Version</b>	with iris feather
<b>Cable sheath</b>	abgesetzt
<b>Thread (AG)</b>	PG 42
<b>Type of packaging</b>	10
<b>Screen diameter max.-min.</b>	39 - 33 mm
<b>Temperature resistant</b>	-20 °C - 105 °C
<b>Material</b>	Nickel-plated brass

## More images

