

# HIL-SHRINK® 2:1 Heat Shrinkable Tubing, 76,2/38,1 black | black

**Product number** 30240

**Weight** 6.658kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

## Product description

Thin wall flexible heat shrinkable tubing.

- shrink ratio: 2:1
- permanent operating temperature: -55 °C up to +125 °C
- material: polyolefin cross-linked
- shrink temperature: +120 °C

## Product properties

|                                         |                                   |
|-----------------------------------------|-----------------------------------|
| <b>Shrinking temperature</b>            | 120 °C                            |
| <b>min. at delivery Ø D</b>             | 3 Zoll                            |
| <b>Type of packaging</b>                | 30                                |
| <b>Colour</b>                           | black                             |
| <b>Approvals</b>                        | UL 224                            |
| <b>Shrink ratio</b>                     | 2:1                               |
| <b>Huges after shrink op. s</b>         | 1,3 mm                            |
| <b>Material</b>                         | Polyolefin radiation cross-linked |
| <b>min. at delivery Ø D</b>             | 76,2 mm                           |
| <b>Continuous operating temperature</b> | -55 °C - 125 °C                   |
| <b>Flexibility</b>                      | thin-walled                       |
| <b>max after shrink operation Ø d</b>   | 38,1 mm                           |
| <b>material properties</b>              | self-extinguishing                |
| <b>Version</b>                          | Coil                              |

## More images

