

HP-ECO Insulators, M 6 red 25 mm

ECO Isolatoren

Product number 91030

Weight 0.466kg



Illustrations are for reference only. Technical specifications may vary and are subject to change without notice.

Product description

- **Insulation:**
 - thermosetting polyester reinforced with 20% fiberglass
 - self-extinguishing: V0-UL94
 - colour: Red RAL 3031
- **Threaded inserts:**
 - galvanized steel
- **Final product:**
 - rated voltage: 1000 V AC/1500 V DC
 - working temperature: -40 °C up to +130 °C

Product properties

| | |
|---------------------------------------|---|
| D | 18 mm |
| Threaded bolt material | Galvanized steel |
| Colour | red |
| Typ | ECO |
| Insulation material properties | self-extinguishing , reinforced with 20 % glass fiber |
| Flame retardancy | UL 94 V-0 |
| Temperature resistant | -40 °C – 130 °C |
| Insulation material | Thermosetting polyester resin |
| R.T. | 3,4 kN |
| R.C. | 29 kN |
| max. indicate torque | 10 Nm |
| Thread (M) | M6 |
| R.F. | 2,2 kN |
| Type of packaging | 20 |
| e | 6 mm |
| Rated voltage DC | 1500 V |
| H | 25 mm |
| CH | 22 mm |
| f | 7 mm |
| Nominal voltage AC | 1000 V |

More images

