

# HIL-SHRINK® CFW 3:1 Heat Shrinkable Tubing, medium wall 33/8,0 black

CFM 3:1 mittelwandig, schwer entflammbar

**Product number** 34120

**Weight** 0.21kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

Medium wall (CFM) heatshrinkable polyolefin adhesive lined tubing ideal for the protection of cable joints and terminations in low voltage power up to 600V.

Applications acc. to ESI-09-11, VDE 0278-95

- shrint ratio: app. 3:1
- permanent operating temperature: -55 °C up to +110 °C
- material: polyolefin cross-linked
- shrink temperature: +120 °C
- UV-resistant

## Product properties

|   |                                   |
|---|-----------------------------------|
| <b>Shrinking temperature</b>            | 120 °C                            |
| <b>max after shrink operation Ø d</b>   | 8 mm                              |
| <b>Version</b>                          | sections                          |
| <b>Continuous operating temperature</b> | -55 °C - 110 °C                   |
| <b>Shrink ratio</b>                     | 3:1                               |
| <b>Colour</b>                           | black                             |
| <b>Section length</b>                   | 1 m                               |
| <b>Type of packaging</b>                | 1                                 |
| <b>Flexibility</b>                      | medium-walled                     |
| <b>Material</b>                         | Polyolefin radiation cross-linked |
| <b>min. at delivery Ø D</b>             | 33 mm                             |
| <b>Huges after shrink op. s</b>         | 2,0 mm                            |
| <b>Excess length</b>                    | T                                 |

## More images

