

# Spacing insulator type DP/P, M6, red, 30 mm

TYP DB/P

**Product number** 90033

**Weight** 3.446kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

- made of Polyglas-polyester material
- reinforced with fibreglass
- colour: red
- self extinguishing
- operating temperature:  $-40\text{ °C} < T < +130\text{ °C}$
- fire resistance: UL94-V0
- UM = max. permissible operating voltage

## Product properties

<b>A</b>	8 mm
<b>max. pressure-carrying capacity</b>	44 kN
<b>Creep strength</b>	8 kV
<b>Threaded bolt material</b>	Galvanized steel
<b>Colour</b>	red
<b>Type of packaging</b>	80
<b>Insulation material properties</b>	self-extinguishing , Reinforced with glass fiber
<b>d1</b>	26 mm
<b>H</b>	30 mm
<b>Insulation material</b>	Polyglass-polyester compound
<b>Flame retardancy</b>	UL 94 V-0
<b>max. bending force</b>	2,5 kN
<b>Typ</b>	DB/P 30
<b>Temperature resistant</b>	-40 °C - 130 °C
<b>max. pulling force</b>	5 kN
<b>U_M</b>	600 V
<b>Thread (M)</b>	M6
<b>Discharge voltage</b>	23 kV
<b>SW</b>	30 mm
<b>max. indicate torque</b>	8,9 Nm

### More images

