

# Spacing insulator type CO/P, M6, red, 40 mm

TYP CO/P

**Product number** 90077

**Weight** 3.856kg



Illustrations are for reference only.  
Technical specifications may vary and  
are subject to change without notice.

## Product description

- made of polyglass-polyester material
- reinforced fibre glass
- self extinguishing.
- operating temperature:  $-40\text{ }^{\circ}\text{C} < T < +130\text{ }^{\circ}\text{C}$
- fire resistance: UL94-V0
- threaded bolt: galvanised steel
- UM = max. operating voltage

## Product properties

<b>Diameter</b>	20 mm
<b>Creep strength</b>	8 kV
<b>max. pressure-carrying capacity</b>	21 kN
<b>Threaded bolt material</b>	Galvanized steel
<b>Colour</b>	red
<b>SW</b>	21 mm
<b>Insulation material properties</b>	self-extinguishing , Reinforced with glass fiber
<b>Insulation material</b>	Polyethylene
<b>max. pulling force</b>	4 kN
<b>Flame retardancy</b>	UL 94 V-0
<b>Temperature resistant</b>	-40 °C - 130 °C
<b>H</b>	40 mm
<b>max. bending force</b>	1,5 kN
<b>A</b>	9 mm
<b>U_M</b>	600 V
<b>Thread (M)</b>	M6
<b>Type of packaging</b>	110
<b>Typ</b>	CO/P 40
<b>Discharge voltage</b>	25 kV
<b>max. indicate torque</b>	12 - 16 Nm

## More images

